


Flex-Turn[®] Belt

Maintain product orientation and spacing around corners.

Flex-Turn[®] conveyor belts gently convey products in process around corners while maintaining proper product alignment and spacing. They offer the tightest level transfer and smallest inside turning radius available. Smooth product handling minimises potential damage to delicate products. Our Flex-Turn[®] conveyor belts are specifically designed to work with our Flex-Turn[®] conveyors. Like all of our Flat-Flex[®] belts, Flex-Turn[®] belts are easy-to-clean and maintain.




Advantages

- The Flex-Turn conveyor belt is a unique, tapered pitch, positively driven, stainless steel conveyor belt that does not collapse upon itself to form a radius, thus greatly reducing the potential for damage to products.
- Right- or left-hand direction of travel is available.
- Angles between 45 and 180 degrees may be special ordered for most Flex-Turn Conveyors.

Benefits

- Unique non-collapsing tapered-pitch belt
- Small product transfer possible
- Non-slip positively driven
- Hygienic design, easy to clean and maintain



Specifications

Flex-Turn® belt widths available

Flex-Turn® belts with 406mm inside radius for use on model 616, 716, & 816 conveyors.

Wire Diameter:	1.83mm
Nominal Pitch Variation Across Width:	7.5mm – 20mm

Belt Width (mm)	Inside Radius (mm)	Available Angles
254	406	45° to 180°
406	406	45° to 180°
610	406	45° to 180°
864*	406	45° to 180°
1092*	406	45° to 90°
1270*	406	45° to 90°

*To minimise wire pitch across width these belts are supplied as a 2 part assembly
 Flex-Turn Belts are available for models 316, 416, & 516

Flex-Turn® belts with 812mm inside radius for use on model 632, 732, & 832 conveyors.

Wire Diameter:	2.08mm
Nominal Pitch Variation Across Width:	9.3mm – 19mm

Belt Width (mm)	Inside Radius (mm)	Available Angles
381	812	45° to 180°
622	812	45° to 180°
864	812	45° to 180°

Flex-Turn Belts are available for models 632, 732, & 832

Flex-Turn® belts with 800mm inside radius for use on model 680, 780, & 880 conveyors.

Wire Diameter:	1.6mm
Nominal Pitch Variation Across Width:	6.3mm – 11mm

Belt Width (mm)	Inside Radius (mm)	Available Angles
400	800	45° to 180°
600	800	45° to 180°
900*	800	45° to 90°
1000*	800	45° to 90°

*To minimise wire pitch across width these belts are supplied as a 2 part assembly.
 Flex-Turn Belts are available for models .380, 480, & 580

All belts are available for either Right Hand (Clockwise) or Left Hand (Anti-Clockwise) operation.
 Other variations of width, pitch & wire diameter available to special order. Please contact our Technical Sales Engineers with your details.

