

## Ladder-Flex™ Conveyor

### Enquiry Form

#### Customer Information

Company Name:	
Contact:	
Email Address:	
End User:	
Date:	
Telephone No:	



How much are you thinking about spending on this part of your project?	
When are you thinking about start up? Is this for CapEx planning or an immediate need?	

#### Product Information

Product::		Environmental Temperature :		°C
Size & Shape:		Product Temperature:		°C
Characteristics:	Wet <input type="radio"/> Moist <input type="radio"/> Dry <input type="radio"/> / Soft <input type="radio"/> Firm <input type="radio"/>	Product Pitch:	At Infeed	mm
Product Loading:	Kg/m <sup>2</sup>		At Discharge	mm

#### Conveyor Information

Conveyor Length:	mm overall	Belt Width:	At Infeed	mm
Standard Belt Height:	(970 mm +/- 50mm) Yes <input type="radio"/> No <input type="radio"/>		At Discharge	mm
<i>Note — If non-standard height, please specify in comments section</i>		Debris Slots (Please specify in comments):	Yes <input type="radio"/> No <input type="radio"/>	
Belt Speed/Range:	Metres per Minute	Castors:	Yes <input type="radio"/> No <input type="radio"/>	

#### Drive and Control Options

Electrical Supply:		Motor Required:		Variable Frequency Device (VFD):	
Voltage	V	Standard SEW SA37	Yes <input type="radio"/> No <input type="radio"/>	Control Panel	Yes <input type="radio"/> No <input type="radio"/>
Frequency	Hz	SEW XCO SA37	Yes <input type="radio"/> No <input type="radio"/>	Invertek Optidrive E3	Yes <input type="radio"/> No <input type="radio"/>
Phase	Ph	St/Steel SEW	Yes <input type="radio"/> No <input type="radio"/>	None	Yes <input type="radio"/> No <input type="radio"/>
		None	Yes <input type="radio"/> No <input type="radio"/>		

#### Hygienic Upgrades

Hygienic Bolt Fixings:	Yes <input type="radio"/> No <input type="radio"/>	Sealed Foot Bracket (Not available with castors):	Yes <input type="radio"/> No <input type="radio"/>
------------------------	--	---	--

*As standard, motor and VFD are mounted on right hand side of conveyor, when viewed from infeed.*

*All electrical components are rated for IP66 Ingress Protection. As supplied, conveyor is deemed to be a non-workstation unit.*

#### Comments/Special Requirements