

STRAIGHT CONVEYOR


CUSTOMER INFORMATION

| | |
|---|--|
| Company Name | |
| Contact | |
| Email Address | |
| End User | |
| Date | |
| Telephone Number | |
| How much are you thinking of spending on this part of your project? | |
| When are you thinking about start up? Is this for CapEx planning or immediate need? | |

PRODUCT INFORMATION

| | | | |
|-----------------|--|---------------------------|-------------------|
| Product | | Product Loading | Kg/m ² |
| Size & Shape | | Environmental Temperature | °C |
| Characteristics | Wet <input type="checkbox"/> Moist <input type="checkbox"/> Dry <input type="checkbox"/> / Soft <input type="checkbox"/> Firm <input type="checkbox"/> | Product Temperature | °C |

CONVEYOR INFORMATION

| | | | |
|------------------|-------------------|----------------------|---|
| Belt Width | mm | Belt Type/Mesh | mm |
| Conveyor Length | mm overall | Standard Belt Height | (970mm +/- 50mm) Yes <input type="checkbox"/> No <input type="checkbox"/> |
| Belt Speed/Range | Metres Per Minute | Castors | Yes <input type="checkbox"/> No <input type="checkbox"/> |

* NOTE - If non standard height, or incline/decline is required, please specify in the comments section.* (include flight details, If necessary)

DRIVE & CONTROL OPTIONS

| | | | | | |
|-------------------|----|---------------------|--|---------------------------|--|
| Electrical Supply | | Motor Required | | Variable Frequency Device | |
| Voltage | V | SEW SA37 (Standard) | Yes <input type="checkbox"/> No <input type="checkbox"/> | Control Panel | Yes <input type="checkbox"/> No <input type="checkbox"/> |
| Frequency | Hz | St/Steel SEW | Yes <input type="checkbox"/> No <input type="checkbox"/> | Invertek Optidrive E3 | Yes <input type="checkbox"/> No <input type="checkbox"/> |
| Phase | Ph | None | Yes <input type="checkbox"/> No <input type="checkbox"/> | None | Yes <input type="checkbox"/> No <input type="checkbox"/> |

SPECIAL REQUIREMENTS

As Standard, Motor and VFD are mounted on the right hand side of the conveyor when viewed from the infeed.

All electrical components are rated for IP66 Ingress Protection. As supplied, the conveyor is deemed to be a non-workstation unit

Additional Comments or Special Requirements